

Addendum for Quilting Cotton:

The Carried Away pattern was written for duck cloth, outdoor fabric, or something of a similar weight and weave. If you would prefer to use quilting cotton, however, we have included a revised material and cutting list as well as additional instructions to follow.

Additional Material List:

1/3 Yard of Pellon Fusible Mid to Heavyweight Interfacing (931TD)
1 1/4 Yard Pellon Fusible Fleece Interfacing (987F)

Additional Cutting List:

Outer Bag:

- 2 - 16 1/2" X 18 1/2" - Center Panel (987F)
- 1 - 10" X 35" - Zipper Panel (931TD)
- 1 - 9" X 11 1/2" - Pocket (987F)
- 4 - 17" X 9 1/2" - Side Panel (987F)

Strap:

- 2 - 1 3/4" X WOF" - Strap (987F)

Making the Side Panels:

Before Step 1:

Center and iron fusible fleece to the wrong side of the four Side Panels and the two Center Panels. **NOTE: If desired, quilt Side Panels and Center Panels.**

Adding the Front Pocket:

Before Step 6:

Iron fusible fleece to the wrong side of the Pocket leaving a 1/2" space on the bottom. **NOTE: If desired, quilt Pocket.**

Attaching the Outer Bag and Lining:

Step 4:

Center and fuse a Buttonhole Stabilizer interfacing piece behind all four lines you drew. **NOTE: You do not have to do this Step if you are using quilting cotton.**

Adding the Zipper:

Before Step 1:

Iron interfacing to the wrong side of the Zipper Panel.

Step 11:

Center and fuse an interfacing piece to the wrong side of the Zipper Panel behind all four lines you drew. **NOTE: You do not have to do this Step if you are using quilting cotton.**